

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp

quality.always

MJ-102. MITASU GOLD SN 0W-20 100% Synthetic

MITASU GOLD SN OW-20 100% Synthetic is a fully synthetic resource conserving motor oil and meets the GF-5 standard for engine oils, set by the International Lubricants Standardization and Approval Committee (ILSAC). The newest ZDDP anti-wear additive package delivers the latest development in lubricating technology to maximize protection and cleanliness for the newest gasoline-fuelled engines.

APPLICATION

MITASU GOLD SN OW-20 100% Synthetic has been designed for modern cars and exceeds the most demanding requirements for modern engine emission control and fuel efficiency. It provides protection from oxidation. It has been designed for all-season use.

SPECIFICATIONS / APPROVALS

- · API SN
- ILSAC GF-5
- dexos1

APPLICATION BENEFITS

All-season MITASU GOLD SN 0W-20 100% Synthetic provides:

- · Easy cold start in winter
- · Significant fuel economy
- · Maximum engine cleanliness
- · Seal protection
- · Extended drain interval

The ZDDP anti-wear additive package deposits much less phosphorous on the face of the catalyst, significantly reducing the poisoning of the catalyst system.

The latest technologies of MITASU OIL CORPORATION, Japan and the ILSAC GF-5 standard enable MITASU GOLD SN 0W-20 100% Synthetic to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, HONDA, ACURA, NISSAN, MAZDA, SUZUKI, MITSUBISHI, SUBARU, DAIHATSU, GM and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	OW-20
Density at 15°C	ASTM D-4052	0,8500
Flash point, °C	ASTM D-92	220
TBN (mg KOH/g)	ASTM D-2896	7,00
Pour point, °C	ASTM D-97	-40
Colour	ASTM D-1500	2,0
Viscosity index	ASTM D-2270	170
Kinematic viscosity at 40°C (cSt)	ASTM D-445	44,10
Kinematic viscosity at 100°C (cSt)	ASTM D-445	8,41

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2023 Mitasu Oil Corporation, Japan.







5L



20L



200L



