



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-221. MITASU SUPER DIESEL CI-4 10W-30 Synthetic Blended

MITASU SUPER DIESEL CI-4 10W-30 Synthetic Blended, is Long Life diesel oil formulated with synthetic base fortified with highly technological additives, designed to improve the energy saving, viscosity-temperature and anti-wear properties of the product. It ensures excellent protection of heavy-duty diesel engines manufactured in Japan, European Union and the USA, even at extended service intervals.

APPLICATION BENEFITS

MITASU SUPER DIESEL CI-4 10W-30 Synthetic Blended is designed for all year round use in high-power and high-speed turbocharged and non-turbocharged diesel engines. It is suitable for use in modern high performance passenger vehicles, vans, SUVs and light trucks. Operational and environmental characteristics of the product meet the modern requirements of the API and OEM around the world.

SPECIFICATIONS / APPROVALS

- API CI-4/SL
- ACEA E7-12
- CATERPILLAR ECF-1A
- CATERPILLAR ECF-2
- CUMMINS CES 20078
- DETROIT DIESEL 93K215
- DEUTZ DQC III-10
- GLOBAL DHD-1
- MACK EO-N, EO-M Plus
- MAN M3275
- MB-Approval 228.3
- MTU Type 2
- RENAULT RLD-2
- VOLVO VDS-3



APPLICATION BENEFITS

Semi-synthetic diesel oil MITASU SUPER DIESEL CI-4 10W-30 Synthetic Blended provides:

- A stable oil film protecting engine parts
- Extended oil drain interval
- Easy engine start at low temperatures
- High fuel efficiency
- Low oil consumption through burning

Ideally suited to modern diesel engines with EGR (exhaust gas recirculation).

The latest technologies of MITASU OIL CORPORATION, Japan enable engine oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, NISSAN, MITSUBISHI, MAZDA, ISUZU, HYUNDAI, KIA, FORD, GM, VW, FIAT, VOLVO, MERCEDES-BENZ and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	10W-30
Density at 15°C	ASTM D-4052	0,8620
Flash Point, °C	ASTM D-92	214
TBN (mg KOH/g)	ASTM D-2896	10,20
Pour Point, °C	ASTM D-97	-36
Colour	ASTM D-1500	<3,5
Viscosity index	ASTM D-2270	158
Kinematic viscosity at 40°C (cSt)	ASTM D-445	71,10
Kinematic viscosity at 100°C (cSt)	ASTM D-445	11,60

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2016 Mitsuo Oil Corporation, Japan.



1L



4L



6L



20L



200L