



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-332. MITASU ATF SP-IV Synthetic Tech



1L



4L



20L



200L

MITASU ATF SP-IV Synthetic Tech is a low viscosity automatic transmission fluid made based on synthetic technology. The product has excellent anti-vibration properties. It complies with international standards and requirements of HYUNDAI and KIA for the ATF SP-IV type automatic transmission fluids. Product colour is red.

APPLICATION

MITASU ATF SP-IV Synthetic Tech is designed for modern automatic transmissions of HYUNDAI and KIA vehicles. It can also be used in automatic transmissions of other car manufacturers where ATF SP-IV fluid is recommended.*

* MITASU ATF SP-IV Synthetic Tech fluid is NOT interchangeable with the original SPH-IV-RR (OEM N°00232-19052) fluid

THIS PRODUCT MEETS THE REQUIREMENTS OF

- HYUNDAI / KIA ATF SP / SPH-IV
- HYUNDAI / KIA 00232-19045
- HYUNDAI / KIA 04500-00115
- HYUNDAI / KIA UM090-CH042



APPLICATION BENEFITS

MITASU ATF SP-IV Synthetic Tech provides:

- Fuel efficiency
- OEM (Original Equipment Manufacturer) specified quality
- Stable performance in a wide range of temperatures
- Improved anti-vibration properties
- Proper functioning of automatic transmissions under various operating conditions
- Excellent wear protection

The latest technologies of MITASU OIL CORPORATION, Japan enable automatic transmission fluids manufactured by the company to exceed the requirements of car manufacturers such as HYUNDAI, KIA and others.

TECHNICAL CHARACTERISTICS

Technical Properties	Method	Result
Density at 15°C	ASTM D-4052	0,8487
Flash point, °C	ASTM D-92	210
Pour point, °C	ASTM D-97	-45
Colour	Visual	Red
Viscosity index	ASTM D-2270	176
Kinematic viscosity at 40°C (cSt)	ASTM D-445	27,44
Kinematic viscosity at 100°C (cSt)	ASTM D-445	6,04

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2023 Mitsuo Oil Corporation, Japan.