



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-333. MITASU ATF MATIC J Synthetic Blended



1L



4L



20L



200L

MITASU ATF MATIC J Synthetic Blended is an automatic transmission fluid featuring synthetic technology and designed for NISSAN vehicles where NISSAN MATIC FLUID J, K, D is recommended. The product has excellent anti-vibration properties and complies with international standards and requirements of NISSAN and JATCO for NISSAN MATIC FLUID J type automatic transmission fluids. The product colour is red.

APPLICATION

MITASU ATF MATIC J Synthetic Blended is designed for JATCO automatic transmissions used in NISSAN, INFINITI and RENAULT vehicles. It can also be used in automatic transmissions of other cars manufacturers where NISSAN MATIC FLUID J, K, D is recommended.

THIS PRODUCT MEETS THE REQUIREMENTS OF

- NISSAN MATIC FLUID J
- NISSAN KLE23-00002
- NISSAN KLE23-00020
- NISSAN KE908-99932
- NISSAN 999MP-MTJ00P
- NISSAN MATIC FLUID K
- 999MP-MTK00P
- NISSAN MATIC FLUID D
- KLE22-00004
- KLE22-00002
- KE908-99931R
- KLE2A-00001
- 999MP-AA100P



APPLICATION BENEFITS

MITASU ATF MATIC J Synthetic Blended provides:

- OEM (Original Equipment Manufacturer) specified quality
- Stable performance in a wide range of temperatures
- Improved anti-vibration properties
- Proper functioning of automatic transmissions under various operating conditions
- Excellent wear protection

The latest technologies of MITASU OIL CORPORATION, Japan enable automatic transmission fluids manufactured by the company to exceed the requirements of car manufacturers such as NISSAN, INFINITI, RENAULT and many others.

TECHNICAL CHARACTERISTICS

Technical Properties	Method	Result
Density at 15°C	ASTM D-4052	0,8650
Flash point, °C	ASTM D-92	195
Pour point, °C	ASTM D-97	-45
Colour	Visual	Red
Viscosity index	ASTM D-2270	168
Kinematic viscosity at 40°C (cSt)	ASTM D-445	33,39
Kinematic viscosity at 100°C (cSt)	ASTM D-445	7,39

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2017 Mitasu Oil Corporation, Japan.