



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-DT3. MITASU BRAKE FLUID DOT 3



0,5 L

MITASU BRAKE FLUID DOT 3 is a premium quality glycol-based brake fluid designed for use in a wide range of loads and temperatures. Featuring extremely stable properties, this product has no aggressive effect on materials used in the making of modern car brake systems. Compared to most traditional fluids, this product has a higher boiling point and excellent low-temperature properties.

APPLICATION

MITASU BRAKE FLUID DOT 3 is intended for use in disc and drum brake systems of modern cars, minivans, SUVs and light commercial vehicles with and without an anti-lock braking system (ABS, ALB, C-ABS, etc.), where the manufacturer recommends DOT 3 fluids. The product maintains high performance over time in a wide range of climatic conditions, high humidity, and at extremely high and low ambient temperatures.

SPECIFICATIONS / APPROVALS

· DOT 3

BENEFITS

MITASU BRAKE FLUID DOT 3 provides:

- Superior performance, exceeding DOT 3 specification requirements
- Stable operational properties in a wide range of temperatures
- Long lasting high performance
- Can be mixed with all glycol brake fluids
- Compatible with all materials used in modern brake systems

The latest technologies of MITASU OIL CORPORATION, Japan enable the brake fluids manufactured by the company to exceed the requirements of FMVSS 116, JIS K 2233, ISO 4925, SAE J 1703 and other standards.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	1,072
DERBP °C	FMVSS-116	254
WERBP °C	FMVSS-116	149
Effect on breaking performance at 70°C	FMVSS-116	None
Effect on rubber components at 120°C	FMVSS-116	None
Colour	Visual	Clear Yellowish
Kinematic viscosity at -40°C (cSt)	ASTM D-445	1370,00
Kinematic viscosity at 100°C (cSt)	ASTM D-445	1,90

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2021 Mitsuru Oil Corporation, Japan