



quality.always

# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
 Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
 E-mail: info@mitasuoil.co.jp

## MJ-329G. MITASU CVT ULTRA FLUID 100% Synthetic

MITASU CVT ULTRA FLUID 100% Synthetic (sub-type of MJ-329G) is a green colour transmission fluid for the continuously variable transmissions (CVT), manufactured from fully synthetic base oils. Use of the unique enhancing additives system allowed to provide the product with exceptional anti-vibration properties and to ensure it meets the highest requirements of OEM manufacturers.

### APPLICATION

The MJ-329G product properties are optimized, factoring in design features of SUBARU CVT's (where the use of CVT OIL for LINEARTRONIC and CVT C-30 special fluids is recommended) and the requirements from manufacturers such as BMW, AUDI, VW, FORD, NISSAN. It is suitable for CVT designs - both push belt and chain continuously variable transmissions.

For routine maintenance of CVT, it is recommended to take your vehicle to a specialized service center that has the equipment to replace 100% of the liquid. If you can't have a complete fluid replacement at a specialized service center, we recommend a minimum double fluid change by draining-filling method at no more than 100km intervals between replacements.

### MJ-329G MEETS THE REQUIREMENTS OF

- SUBARU CVT OIL for LINEARTRONIC (K0425Y0710/11)
- SUBARU CVT C-30 (SOA868V9245)
- NISSAN CVT Fluid NS-2 (KLE52-00004)
- BMW CVT EZL 799A (83 22 0 429 154)
- AUDI G 052-180 (TL 521 80)
- VW G 052-180 (TL 521 80)
- FORD CVT WSS M2C928-A
- FORD CVT WSS M2C933-A
- MOPAR CVTF +4
- FULL APPLICATION LIST OF MJ-322



1L

4L

20L

200L

### APPLICATION BENEFITS

MITASU CVT ULTRA FLUID 100% Synthetic provides:

- Compliance with the highest requirements of manufacturers of OEM (Original Equipment Manufacturer)
- Exceptional anti vibration properties
- Proper operation of a variable speed type transmissions in various types of operating modes
- Stable performance characteristics in a wide range of temperatures

Designed with use of the latest technologies, MITASU CVT ULTRA FLUID 100% Synthetic exceeds the requirements of Japanese, European and American (OEM) manufacturers and can be used in CVT vehicles made by other manufacturers. The full list of this product application includes all recommendations for MJ-322

### TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8530
Flash point, °C	ASTM D-92	201
Pour point, °C	ASTM D-97	-45
Colour	Visual	Green
Viscosity index	ASTM D-2270	193
Kinematic viscosity at 40°C (cSt)	ASTM D-445	31,30
Kinematic viscosity at 100°C (cSt)	ASTM D-445	6,95

Due to continual product research and development, the information contained herein is subject to change without notification.