



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-V11. MITASU EURO OIL LL III 5W-30 100% Synthetic



1L



4L



20L



200L

MITASU EURO OIL LL III 5W-30 100% Synthetic is a fully synthetic energy saving motor oil of Low SAPS grade. It is developed from a high quality GTL (Gas to Liquid) base oil combined with a modern system of enhancing additives with low levels of phosphorus and sulfur. It meets the EURO VI standard, including vehicles fitted with diesel particulate filters (DPF) and/or three-way catalysts.

APPLICATION

MITASU EURO OIL LL III 5W-30 100% Synthetic is ideal for modern cars powered by gasoline and diesel engines with or without turbocharging, direct injection and multi-stage emission-reducing systems. The performance and environmental characteristics of the product meet most of the requirements of Japanese, European and American automotive manufacturers as well as the API and ACEA standards. It is designed for year-round use and is suitable for all engines requiring ACEA C3 oil. This product is also suitable for engines that require MB-Approval 229.51, MB-Approval 229.31 and ACEA C2 specifications.

SPECIFICATIONS / APPROVALS

- API SP/CF
- ACEA C3
- GM dexos2
- FIAT 9.55535-S3/S1
- OPEL OV 040 1547-G30/D30
- MB-Approval 229.52
- VW 504.00/507.00
- BMW Longlife-04
- PORSCHE C30
- PSA B71 2297



APPLICATION BENEFITS

All-season fully synthetic motor oil MITASU EURO OIL LL III 5W-30 100% Synthetic provides:

- Stable performance in a wide range of temperatures due to GTL base oil
- Low Speed Pre-Ignition (LSPI) protection of new generation T-GDI engines
- The level of quality specified by OEM
- Significant extension of drain interval
- Extended life of diesel particulate filters (DPF) and catalytic converters

The latest technologies of MITASU OIL CORPORATION, Japan enable MITASU EURO OIL LL III 5W-30 100% Synthetic to meet the requirements of such car manufacturers as AUDI, SEAT, SKODA, RENAULT, CHEVROLET, CITROEN, PEUGEOT and many others

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	5W-30
Density at 15°C	ASTM D-4052	0,8437
Flash point, °C	ASTM D-92	220
TBN (mg KOH/g)	ASTM D-2896	7,50
Pour point, °C	ASTM D-97	-40
Colour	ASTM D-1500	<3,5
Viscosity index	ASTM D-2270	173
Kinematic viscosity at 40°C (cSt)	ASTM D-445	68,36
Kinematic viscosity at 100°C (cSt)	ASTM D-445	11,94

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2024 Mitasu Oil Corporation, Japan.