

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan

Tel: +81-3-5532-8187. Fax: +81-3-5532-8188

E-mail: info@mitasuoil.co.jp

MATERIAL SAFETY DATA SHEET

1	PRODUCT IDENTIFICATION AND COMPANY												
	Issue Date	05.11.2024											
	Validity Period	3 years											
	Product Name	MJ-	N11.	MITAS	U M	OLY-TRIME	R SN/CF 5	W-30	100% Synthetic				
_	Product Code	MJ-	N11										
	Producer	Mita	su O	il Corp	ora	tion							
		1-2-9, Nishi Shimbashi, Minato-Ku,Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp											
2	COMPOSITION												
_		lasi			101								
	Base Oil Content	80	_	85	%								
	Additives Content	15	-	20	%								
3	HAZARDS IDENTIFICATION												
_	Human Health	Product is not hazardous.											
	Eye Contact	Slig	htly ir	ritant.									
	Inhalation	Rep	ts may cause irritation of	or discomfort.									
_	Ingestion	Minimal toxicity.											
	Safety Hazards	Not classified as flammable but will burn.											
Environmental Not readily biodegradable. Hazards													
4	FIRST AID												
	Eye Contact			es with		e amount of v	water until	irritatio	on subsides. If irritation	persists, get			
Skin Contact Flush with large amount of water; use soap if available. Remove contartivitation persists, get medical attention. Inhalation Remove to fresh air. If rapid recovery does not occur, get medical attertion. Do not induce vomiting. If rapid recovery does not occur, get medical attertion.								lable. Remove contamir	nated clothing. If				
								cur, get medical attentic	n.				
								occur, get medical atte	ntion.				
J	FIRE SAFETY												
	Flash Point		211	°C									

	Flammable Limit			lazardous combustion products may inc nidentified organic and inorganic compo							
_	Autoignition Temp	>	306 °C								
	Specific Hazards	Not classified as flammable but will burn. Hazardous combustion products may include carbon monoxide, oxides of sulphur, and unidentified organic and inorganic compounds.									
	Fire Fighting	fro		ter to cool and protect fire-	to extinguish fire. Water may cause spla exposed material. Wear protective equi						
6	ACCIDENTAL RELEASE MEASURES										
	Clean-up Procedure	an	ount of inert a	absorbent material such as	tain spill if possible. Cover spill with ger s sand or earth. Sweep up and remove to sosal in accordance with local regulati.						
7	HANDLING AND STOR	AGE									
	Handling Handling temperatures should not exceed 70°C. Wear proper safety protective equipment. Wash hands thoroughly after handling. Water contamination and spillage should be avoided.										
	Storage	Storage temperatures should be maintained between 0 to 50°C. Odorous and toxic fumes may be evolved from decomposition of product if stored above the safe temperature.									
8	EXPOSURE CONTROL/PERSONAL PROTECTION										
	Exposure Limits	Threshold Limit Values for oil mist is recommended to be controlled at 5 mg/m3 or lower for exposure of 8 hours daily.									
	Ventilation	Exhaust ventilation to keep below exposure limits.									
	Eye Protection	Wear safety glasses or face shields if splashing is likely to occur.									
	Skin Protection	Av	oid repeated a	and prolonged contact with	product. Use oil resistant gloves.						
	Respiratory Protection	Not normally required unless in confined space.									
	Body Protection	Use proper protective equipment to avoid contact. Wear PVC apron if splashes are likely to occur.									
9	PHYSICAL AND CHEM	ICAL	PROPERTIES	S							
	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not be construed as guaranteeing any specific property of the product.										
	TEST DESCRIPTION		UNIT	METHOD	TYPICAL RESULTS						
_	Appearance		-	Visual	B & C						
					0.0						
	Color		-	D 1500	<3,0						
	Color Density at 15 °C	0.80	kg/l	D 4052	0,8498						
	Color	0°C	kg/l cSt		•						
	Color Density at 15 °C Kinematic Viscosity at 4 Kinematic Viscosity at 1 °C		-	D 4052 D 445 D 445	0,8498 63,50 11,17						
	Color Density at 15 °C Kinematic Viscosity at 4 Kinematic Viscosity at 1 °C Viscosity Index		cSt cSt	D 4052 D 445 D 445 D 2270	0,8498 63,50 11,17						
	Color Density at 15 °C Kinematic Viscosity at 4 Kinematic Viscosity at 1 °C		cSt	D 4052 D 445 D 445	0,8498 63,50 11,17						
	Color Density at 15 °C Kinematic Viscosity at 4 Kinematic Viscosity at 1 °C Viscosity Index		cSt cSt	D 4052 D 445 D 445 D 2270	0,8498 63,50 11,17						
	Color Density at 15 °C Kinematic Viscosity at 4 Kinematic Viscosity at 1 °C Viscosity Index Total Base Number		cSt cSt - mgKOH/g	D 4052 D 445 D 445 D 2270 D 2896	0,8498 63,50 11,17 171 7,70						

10	STABILITY AND REACT	TIVITY										
	Stability Product is stable under normal use conditions.											
	Thermal Decomposition	Carbon monoxide, carbon dioxide, oxides of sulphur and nitrogen and organic and inorganic compound may evolve when subject to heat or combustion.										
	Hazardous Polymerisation	Will not occur under normal conditions.										
	Incompatible Materials	Strong oxidizing agents. Strong acids										
1	TOXICOLOGICAL INFORMATION											
	Basis	No toxicological data is available for this product. Information is provided based on the additives, other components and base stock used.										
	Acute Exposure Oral	LD 50 expected to be above 2000 mg/kg										
	Acute Exposure Skin	LD 50 expected to be above 2000 mg/kg										
	Inhalation	Repeated or prolonged exposure to oil mists may cause irritation.										
	Eye Irritation	Slightly irritant.										
	Skin Irritation	Not a skin irritant unless repeated or prolonged contact.										
	Respiratory Irritation	Slight irritant.										
	Carcinogenicity	No data to suggest that product is carcinogenic.										
	Mutagenicity	No data to suggest that product is mutagenic.										
	Other Information	Brief contact with used oil is not expected to have serious effect in humans if the oil is removed thoroughly by washing with soap and water.										
		Used engine oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they present risks to health and the environment on disposal. All used oils should be handled with caution.										
2	ECOLOGICAL INFORMATION											
	Basis	No ecological data is available for this product. Information is provided based on the additives, other components and base stock used.										
	Mobility	Liquid under most environmental conditions. Floats on water. It is absorbed by soil and will not be mobile.										
	Persistence/ Degradability	Not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.										
	Bioaccumulation	Has the potential to bioaccumulate.										
	Ecotoxicity	Poor soluble mixture. Practically non-toxic to aquatic organisms. May cause physical fouling of aquatic organisms.										
3	DISPOSAL CONSIDERATION											
	Product Disposal	Used or waste oil should be recycled or disposed off in conformity to local disposal regulations. Contact local authorities for approved disposal contractor.										
	Container Disposal	Empty drums should be completely drained and sent to a drum reconditioner or properly disposed of. Non-reusable small containers should be recycled or disposed of. Ensure conformity to local disposal regulations.										

14	TRANSPORT INFORMATION											
	General Information	Not dangerous for conveyance under UN, IMO, ADR/RID and IATA/ICAO codes.										
15	REGULATORY INFORMATION											
	Not Applicable.											
16	OTHER INFORMATION											
	The above information is based on data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with											

The above information is based on data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose. Therefore, no warranty either express or implied of merchantability or fitness for particular purpose is made with respect to the product or the information contained herein.